

# Mappings

- [Using Mappings](#)
  - [XporterTemplate Mappings](#)
- [Custom Field Mappings](#)
- [Jira Agile Epic Link](#)

## Using Mappings

To use a mapping, just open your template document and type the mapping using the following notation:

```
{<Field>}
```

The available keywords are listed in the following table:



Please check the [Deprecated Mappings](#) page to ensure you are using the most recent mappings.

Field	Content
AffectedVersions	The project versions affected by the issue (a list with 1 version per line).
AffectedVersionsList	The project versions affected by the issue (separated by commas).
AggregateOriginalEstimate	The sum of originally estimated time for issue completion, in seconds.
AggregateOriginalEstimateFormatted	The sum of originally estimated time for issue completion formatted as defined in the <a href="#">Jira Time Tracking</a> options.
AggregateRemainingEstimate	The sum of remaining estimated time for issue completion, in seconds.
AggregateRemainingEstimateFormatted	The sum of remaining estimated time for issue completion formatted as defined in the <a href="#">Jira Time Tracking</a> options.
AggregateTimeSpent	The sum of time spent working on the issue, in seconds.
AggregateTimeSpentFormatted	The sum of time spent working on the issue formatted as defined in the <a href="#">Jira Time Tracking</a> options.
AssigneeId	The issue assignee ID.
AssigneeUserDisplayName	The issue assignee Jira display name.
AssigneeUserEmailAddress	The issue assignee Jira email address.
AssigneeUserName	The issue assignee Jira username.
AssigneeGroups	The groups to which the issue assignee belongs.
Attachments	The attachments of the current issue (a list with 1 attachment per line). <b>Note:</b> You can iterate over Attachments and get some metadata from them.
AttachmentsCount	Returns the number of attachments in the Issue.
BelongsToEpic	Returns "true" if the current issue belongs to an Epic Issue; otherwise, it returns "false".
BulkIssueIndex	The index/position of the current issue being mapped. Usable only in bulk export. 0 is the index for the first issue.
BulkIssuesCount	The number of issues selected in a bulk export. Usable only in bulk export.
CommentsCount	Returns the number of comments in the Issue.
Components	The components to which an issue belongs.
ComponentsCount	Returns the number of components in the Issue.

Created	The issue creation date time in ISO Format. If you want to print only the date, you should use <code>\${dateformat("yyyy-MM-dd"):Created}</code> . If you want to print the date and time, you should use <code>\${dateformat("dd-MM-yyyy HH:mm:ss"):Created}</code>
Current Date	Returns the current date.
Current Date Time	Returns the current date time.
Description	The issue description.
DocumentId	Unique ID generated identifying the document.
Due Date	The issue due date.
Environment	The issue environment.
EstimatedTime	The estimated time for issue completion. <b>Do not use this field as it will become soon deprecated.</b> Use <b>RemainingEstimate</b> .
FilterJQL	Current JQL used to search Issues.
FilterName	Current Filter Name used to search Issues.
FixVersions	The versions an issue fixes.
FixVersionsRelease Date	The release date of the versions an issue fixes.
FixVersionsList	The versions an issue fixes, separated by commas.
FixVersionsRelease DateList	The release dates of the versions being fixed by an issue, separated by commas.
Id	The issue ID. For example, 1.
Images	<p>When used as a single field "<code>{Images}</code>", it renders the images List of images attached to the issue. Images are rendered in an order respecting the creation date.</p> <p>For this field, you are allowed to define extra attributes with the max image width, max image height and the sort order of the images.</p> <p><b>Examples:</b></p> <pre>{Images maxwidth=100 maxheight=100}</pre> <pre>{Images maxwidth=100 maxheight=100 sortby=name}</pre> <pre>{Images maxwidth=100 maxheight=100 sortby=date}</pre> <p><b>Note:</b> You can iterate over images and get some metadata from them.</p>
ImagesCount	Returns the number of images attached to the Issue.
IssueTypeDescription	The issue type description.
IssueTypeDescriptionTranslated	The translated issue type description.
IssueTypeName	The issue type.
IssueTypeNameTranslated	The translated issue type.
Issue Type	The Issues Type name.
Issue Type.Id	The id of the issue type.
Issue Type.Name	The Name of the issue type.
Issue Type.Type	The Type of the issue type.
Issue Type.IconURL	The Icon URL of the issue type.
JQLIssuesCount	The number of the issues returned by the parent JQL Iteration.
Key	The internal issue Key. For example, PROJECT-1.
Labels	The issue labels.

LinksCount	Returns the number of links to the Issue.
OriginalEstimate	The originally estimated time for issue completion, in seconds.
OriginalEstimateFormatted	The originally estimated time for issue completion formatted as defined in the <a href="#">Jira Time Tracking</a> options.
ParentIssueDescription	The parent issue description.
ParentIssueId	The parent issue ID.
ParentIssueKey	The parent issue key.
Priority	The issue priority.
PriorityTranslated	The issue priority translated into the language of the logged user.
PriorityDescription	The issue priority description.
PriorityDescriptionTranslated	The issue priority description translated into the language of the logged user.
Project.Components	The project components an issue belongs.
Project.Category	The issue project category.
Project.Id	The issue project Id.
Project.Key	The issue project key.
Project.Name	The issue project name.
Project.URL	The issue project URL.
Project.Lead	The issue project leader.
RemainingEstimate	The remaining estimated time for issue completion, in seconds.
RemainingEstimateFormatted	The remaining estimated time for issue completion formatted as defined in the <a href="#">Jira Time Tracking</a> options.
ReporterId	The issue reporter ID.
ReporterUserDisplayName	The issue assignee Jira display name.
ReporterUserEmailAddress	The issue assignee Jira email address.
ReporterUserName	The issue reporter Jira username.
ReporterGroups	The groups to which the issue reporter belongs.
Resolution	The issue resolution.
ResolutionTranslated	The issue resolution translated into the language of the logged user.
Resolved	The issue resolution date in ISO format. If you want to print only the date, you should use <b>`\${dateformat("yyyy-MM-dd"):Resolved}</b> .If you want to print the date and time, you should use <b>`\${dateformat("dd-MM-yyyy HH:mm:ss"):Resolved}</b> .
ResolutionDescription	The issue resolution description.
ResolutionDescriptionTranslated	The issue resolution description translated into the language of the logged user.
ResolutionDesc	
SecurityLevel	The issue security level.
SecurityLevelId	The issue security level ID.
Status	The issue status.
StatusTranslated	The issue status translated into the language of the logged user.
StatusTransitionsCount	Returns the number of status transitions of the Issue.

StatusDescription	The issue status description.
StatusDescriptionTranslated	The issue status description translated to the language of the logged user.
Sprint	The Issue Sprint Name.
SubTasks	List of issue subtasks.
SubtasksCount	Returns the number of subtasks of the Issue.
Summary	The issue summary.
TestsCount	Returns the number of Tests in an issue of type Test Set.
TestStepsCount	Returns the number of Test Steps in an issue of type Test.
Time Spent	The time spent working on the issue.
Updated	The issue update timestamp. If you want to print only the date, you should use <code>#{dateformat("yyyy-MM-dd"):Updated}</code> . If you want to print the date and time, you should use <code>#{dateformat("dd-MM-yyyy HH:mm:ss"):Updated}</code> .
UserDisplayName	Display name of the user that is requesting the export.
UserEmailAddress	Email address of the user that is requesting the export.
Username	Username of the user that is requesting the export.
URL	Returns the URL of the Issue detail screen.
Votes	The number of times an issue was voted.
Watches	The number of watches of the issue.
Watchers	Returns a list of Users that are watching the Issue. Functions: <b>fullname</b> and <b>emailaddress</b> can be used with this field.
Commits	The number of commits for this issue.
Branches	The number of branches for this issue.
PullRequests	The number of pull requests for this issue.
Builds	The number of builds for this issue.
Reviews	The number of reviews for this issue.
Parent	Return fields from Parent issues.

## XporterTemplate Mappings

Field	Content
XporterTemplate.Name	The template name.
XporterTemplate.Description	The template description.
XporterTemplate.Type	The template type (Docx, Xlsx, ...).
XporterTemplate.Filename	The template file name.
XporterTemplate.Source	The template installation source (Store, User upload).
XporterTemplate.Creator	The creator of the template.
XporterTemplate.ModifiedBy	Who has modified the template.
XporterTemplate.Created	The template createddate.
XporterTemplate.Updated	The template updated date.

### Expand to see the examples on sample code

```

${XporterTemplate.Name}
${XporterTemplate.Description}
${XporterTemplate.Type}
${XporterTemplate.Filename}
${XporterTemplate.Source}
${XporterTemplate.Creator}
${XporterTemplate.ModifiedBy}
${XporterTemplate.Created}
${XporterTemplate.Updated}

```

## Custom Field Mappings

The Xporter for Jira plugin supports custom fields. To use your own defined custom fields, just use the same notation:

```

${<Custom field name>}

```

The <Custom field name> must match exactly the name on which you created the custom field. Example:

```

${My Special One And Only Custom Field}

```

If you have Custom Fields with the same name, it is possible to explicitly indicate the custom field that you want to export using its internal Jira identifier. You can find the identifier of a custom field, by going to the Jira administration, section fields, and edit the custom field. The id will appear in the URL (ex: <http://jiraserver/secure/admin/EditCustomField!default.jspa?id=10070>). The notation to be used is:

```

${<Custom field name>[<Custom field id>]}

```

### Expand to see the example on sample code

```

${My Custom Field[10070]}

```

The officially supported custom fields are:

- Number Field
- Text Field (read only)
- Text Field (multi-line)
- Group Picker (single group)
- Group Picker (multiple groups)
- User Picker (single user)
- User Picker (multiple users)
- Date Picker
- Date Time Picker
- Select List (single choice)
- Select List (multiple choices)
- URL Field

The plugin may work with other custom fields (even provided by other plugins). This depends on the way other custom field types implement the rendering of the field values.



Custom Fields can also be referenced using their translated name. For example, if a custom field named "Reason" is translated in Jira to French as "Raison", you can refer to the field in the template with `${Reason}` or `${Raison}`.

## Jira Agile Epic Link

The Xporter allows rendering all the fields from the Epic Link for an issue. This Epic Link feature is available with the Jira Agile App.

```

${Epic Link.Field}

```

**Expand to see the examples on sample code**

```
#{Epic Link.Key}  
#{Epic Link.Summary}  
#{Epic Link.LinkType}
```